Martin Lishman

Moisture Meters

















Professional Crop Moisture Measurement

Moisture meters for use in the grain store

PROTIMETER Grainmaster i2-S



Save money with regular servicing

Avoid deductions and the cost of overdrying by cleaning and servicing the Grainmaster i2-S regularly. We service all makes of moisture meter to conform with quality assurance schemes, or you can do a simple calibration check at one of our moisture meter clinics. See our website for further details.

NEW Grainmaster i2 Store Management App

Download moisture and temperature readings instantly using the Grainmaster App. Readings from the meter or any of the optional probes can be sent instantly via Bluetooth to a smartphone, speeding up the recording process and making it easier to provide evidence for crop assurance schemes.

The App allows the user to manage multiple crop stores. Using onscreen store maps monitoring changes to crop moisture or temperature is much simpler. Results can be viewed in the App or exported in either graph or table form. Search *Grainmaster* on the App stores.

App Store

Still BEST for ACCURACY

Built on the foundations of the UK's most popular moisture meter, the Grainmaster i2 offers the same accurate moisture measurement with new enhancements.

It is good practice to use a meter that has a track record for providing consistent, accurate and reliable grain moisture readings during harvest time and throughout drying

Using tried and tested crop calibrations, the robust electronics of the Grainmaster i2 give high levels of repeatability between samples.

The Protimeter Grainmaster i2-S is supplied in a hard carry case with a button dust protector, spare grinder-blade set, spare battery and free first year service voucher.

Key Features

- 15 pre-programmed crop calibrations and 30 reference calibrations
- Easy calibration adjustment facility
- Automatic temperature compensation
- Multi Lingual options
- New keypad design
- Easy read backlit display
- USB connectivity
- Bluetooth enabled



Optional external moisture and temperature probes for grain and straw



Grain Temperature Probe

Fast response 1.5m probe for checking stored grain temperatures. Ideal for quality assurance checks and simple cooling fan management.

Bale Temperature OR Moisture Probe

600mm probes for checking hay and straw bale temperatures or moistures.



PROTIMETER Balemaster



STRONG and EASY to Use

The Protimeter Balemaster is a 2-piece instrument and probe that really stands up to heavy farm and industrial use. Pressure can be used to force the probe into tough bales, without risk to the instrument. Helps decide if bales are in a safe condition to store or for assessment at power station intake points.



Balemaster Key Features

- Self-calibration check shows if device is within specification
- Reference mode simplifies comparing moisture readings
- Upgraded battery lasts 3x longer than the previous model
- Bluetooth connectivity to save and download readings
- Displays bale moisture instantly
- 600mm probe reaches the centre of big bales
- · Suitable for all bales, including Miscanthus
- 0.5% accuracy consistent and reliable results





Ideal for WOODCHIP

The Protimeter Timbermaster is recognised as the best instrument for quick and simple woodchip moisture measurement. Supplied with a strong 600mm moisture probe to withstand heavy-duty use.

Martin Lishman Field Check



Whole Grain Meter

Simple scoop action with built-in pressure indicator and compressor. Results displayed in seconds.



Ideal for the COMBINE

Budget-priced, portable, robust meters ideal for checking trailers or drying progress. With whole or ground grain options, both meters give consistent repeat readings and can be re-calibrated to match other meters.

Martin Lishman Field Check PLUS



Ground Grain Meter

Integral grinding handle with measuring cups to suit the crop and pre-set grinding action. Easy display navigation.

Details and Specifications



Protimeter Grainmaster i2-S (Product Code: GRN3000i2-S)

Features:

15 pre-programmed crop calibrations

- Wheat, Barley, Oats, Oil Seed Rape, Canola, Linseed, Peas, Beans, Maize, Sunflower Seed, Coffee Beans, Soya Beans, Milled Rice, Paddy Rice, Sorghum

30 additional calibrations (see www.martinlishman.com)

Adjustable calibration and 0-100 scale user calibration facility Automatic temperature compensation

Complete service pack

- hard carry case , operating button dust protector, spare grinder blade and feeder ring, spare battery, free first year service voucher (conditions apply).

Multi Lingual Options - EN, FR, DE, SP, IT. Others available to download on request

Optional probes for Grainmaster i2-S



Temperature Probes

Grain Temperature (Product Code: GRN6046)

- 1.5m stainless steel, fast response


Bale Temperature (Product Code: GRN6155)

- 600mm stainless steel , fast response, T-bar handle



Bale Moisture Probe (Product Code: GRN6138)

- 600mm stainless steel probe with strong handle
- Calibrated for wheat straw (suitable for other baled products)
- Adjustable calibration using meter settings



Resolution: 0.1

Operating range: Meter 0 - 40°C

Grain or bale temperature probe 0 - 80°C

Weight (c/w grinder-compressor): 950g

Dimensions (c/w grinder-compressor): 19.5 x 18.5 x 10 cm

Power: 1 x PP3 9V battery (included plus spare)

% Moisture ranges:

Meter only or with moisture/temperature probe for relevant

calibrations (see left)

Barley: 10.9 to 29.3 Beans: 12.4 to 25.0 Canola: 7.0 to 26.0 Coffee: 9.8 to 23.9 Linseed: 7.0 to 16.5 Maize: 10.4 to 26.2 Oats: 10.9 to 29.3 OSR: 7.0 to 26.0 Paddy: 10.4 to 26.2 Peas: 12.0 to 30.9 Rice: 13.2 to 26.5 Sorghum: 10.2 to 26.9 Sova: 7.4 to 22.2 Sunflower: 6.2 to 23.0

Wheat: 11.3 to 29.3

Specifications: Resolution: 0.1 % Moisture range:

Balemaster

With bale moisture probe in wheat straw: 8.5 to 36.8%



Protimeter Balemaster (Product Code: GRN6175)

600mm stainless steel moisture probe with strong handle Calibrated for wheat straw (suitable for other baled products) Auto-off, backlight, buzzer and moisture description functions

Optional Temperature Probes

Bale Temperature (Product Code: GRN6154)

- 600mm stainless steel , fast response, T-bar handle

Grain Temperature (Product Code: GRN6153)

- 1.5m stainless steel, fast response



<u>Protimeter Timbermaster</u> (Product Code: GRN6156)

Features:

600mm stainless steel moisture probe with strong handle Calibrated for wood moisture measurement Auto-off, backlight, buzzer and moisture description functions Optional Temperature Probes available (see Balemaster above)



Dimensions: Meter 19 x 6.5 x 3.5 cm; Probe 600mm long Power: 9V battery (alkaline 550 mAh) (included)

With Bale Moisture Probe in wheat straw: 8.5 to 36.8%

Operating humidity range: 0 - 90% RH (non-condensing)

7 to 29.6% (depending on wood type); relative readings to 99%

Regulatory compliance: CE. RoHS. ETL

Temperature probes: 0 °C to c.80 °C

Weight (with bale moisture probe): 228a

Operating temperature range:

Meter: 0 °C to 50 °C



FieldCheck Whole arain readinas

<u>FieldCheck</u>PLUS

(Product Code: CQ/FIELD) (Product Code: CQ/FIELDPLUS) Ground grain readings



Features:

14/15 pre-programmed crop calibrations:

Wheat, Barley, Oats, Rye, Maize, Oil Seed Rape, Peas, Beans, Triticale, Red fescue, Rye grass, Linseed, Sunflower, Mustard, Blue grass (Field CheckPLUS only)

Automatic averaging function Automatic temperature compensation Adjustable calibration facility Hard carry case

Specifications:

Accuracy: +/- 0.5% by using averaging and self-calibration

% Moisture range: 5-50% (crop dependent)

Operating range: 0 - 50°C

Weight: Field Check 1.6 kg, Field CheckPLUS 1.8 kg **Dimensions:** Meter 13 x 21 x 8 cm; Case 32 x 29 x 12 cm

Power: 1 x PP3 9V battery (included)

Martin Lishman Ltd is the sole UK distributor and service agent of Protimeter products for agriculture

Protimeter, Grainmaster and Balemaster are trade marks of Amphenol Advanced Sensors. Field Check and Field Check PIUS are trade marks of Martin Lishman Ltd. Martin Lishman Ltd reserves the right to alter product specifications at any time without notice. © Martin Lishman Ltd November 2024

Martin Lishman Ltd

Unit 2B, Roman Bank, Bourne, Lincs, PE10 9LQ, UK T: +44 (0)1778 426600 F: +44 (0)1778 426555 E-mail: sales@martinlishman.com

www.martinlishman.com

🄰 @Martin_Lishman

f/martinlishmanltd